

The AMS 1001 Direct Thermal Printer

Features:

- ◆ Prints up to 7,000 address labels per hour
- ◆ 200 dpi print resolutions in a metal case
- ◆ Buffering ensures that there is no delay between labels allowing the AMS 1001 to print up to 4 inches per second
- ◆ Easy label loading and printer operation
- ◆ Ultra high reliability for minimum down- time



Specifications:

- ◆ Print Quality & Speed: 200 DPI – up to 4 inches per second
- ◆ Print Length: Maximum: 16 inches
- ◆ Technology: Direct Thermal
- ◆ Media Sizes: Maximum: 8" long x 4.65" wide and up to 0.01 in thickness
Minimum: 8" long x 0.75" wide and up to 0.0025 in thickness
- ◆ Media Types: Roll or fanfold media; continuous or perforated die-cut labels, tags and tickets.
- ◆ Fonts and Barcodes: 1 scaleable, 8 bitmap
- ◆ Dimensions / Weight: 245 x 207 x 154.5 (mm) – 6.5kg
- ◆ Options: Autocutter, Peeler, External rewinders



Flexibility:

To ensure our printers are compatible with the majority of applications, we include an industry standard emulation in each printer and drivers are available for Windows 95, 98, 2000 and NT4 operating systems. This allows the user to use standard applications or a more sophisticated label design package with ease.